

Mini-Bank

NH-2100T



The Best Value in retail through-the-wall ATM, the NH-2100T offers flexibility for installation with its efficient design

Features

- **Reliability**

NH-2100T meets security standards such as Triple DES compliance and a VISA Encrypting PIN pad. Transreflective LCD display and weatherized construction ensures operation in all climates.

- **Flexibility**

Compact architecture with ergonomic design offers unrivalled flexibility for installation and mounting in all environments.



*Create your true ATM values
Design your own portfolio*



The **NH-2100T** provides outstanding flexibility and reliability to satisfy your requirements.

The **NH-2100T** supports exceptional reliable performance with various components such as standard 2000 note capacity cash dispenser and service panel for monitoring, configuration, diagnostics and maintenance.

Our solution strengthens you to build better customer relationships as well as enhanced technologies

Nautilus
HYOSUNG

Nautilus Hyosung, always by your side



Customer Display

5.7" Monochrome Transreflective LCD

Communication

Dial-up

Optional

TCP/IP

Input Type

4 x 2 Function keys

4 x 4 Numeric keys

Encrypting PIN Pad

(DES,T-DES, Unique Key)

Supervisor Operation

Customer display in common

Optional

Service panel

5.7" mono display

4 x 2 function keys, 16keys

Card Handling

Dip type card reader

Optional

IC card reader

Cash Dispensing

2000 note cassette

200 notes reject bin

Printers

Thermal receipt printer

Security

UL291 business hour vault

Dial Lock

Optional

Electronic Safe Lock

KABA Mas Cencon Safe Lock

Miscellaneous

Illuminated signage

Optional

Adjustable pedestal

Power Supply

AC 110~230V, 50~60Hz

Operating Environment

Temperature

40°F~95°F (5°C ~ 35°C)

Humidity

15%~85%

Dimension and Weight

Height : 31.5" (800mm)

Width : 20" (508mm)

Depth : 28.5" (724mm)

Weight : 283 lbs (128kg)

Wall thickness : 4" ~ 10"

※ New technologies and components may be implemented in the products without prior notice, so Nautilus Hyosung reserve the right to change specifications accordingly.

